



DATA SHEET



Model: **BLCF 360**

Basic Laboratory Chest Freezer



TECHNICAL CHARACTERISTICS:

- **Structure** : completely in sheet steel white epoxy coated (rust-proof material) outside, and embossed aluminium inside. All the internal corners are rounded to make easy any cleaning operation
- **Insulation** : high density (40 Kg/m³) foamed-in-place polyurethane, with a thickness of 70 mm. CFC-free
- **Rollers** : Nr 4 to make easy any moving required
- **Lid** : Nr 1 hinged, fully insulated, realized in sheet steel white epoxy coated outside and atoxic plastic material inside. The lid is fitted up with counterbalanced hinges (to avoid unexpected lid closing), perimetric magnetic rubber gasket (granting a perfect seal) and security key locking
- **Internal equipment** : Nr 2 open wire basket made in sheet steel white enamelled. The basket is supported by a special profile inside the freezer
- **Internal lighting** : Nr 1 bulb, mounted in the internal side of the lid, with automatic activation at every door opening through a special switch
- **Control panel** : incorporated in the handle, with soft-touchpads controls. The control panel includes:
 - **Serie of LED with pre-fixed temperatures** : Showing the actual internal temperature and through the setting buttons is possible to select the desired temperature within the pre-fixed steps
 - **Alarm functions** : both visual (with a red colour LED) and acoustic (through a buzzer) , signalling when the temperature is too high or too low. The intervention limits are factory setted and not adjustable. The alarm works only in case of presence of the main
 - **Superfreezing** button : increasing the freezing capabilities in case of new material to be frozen
- **Cooling unit** : compound by a hermetically sealed compressor (placed in the bottom right part of the cabinet), a condenser (located in the back side of the cabinet) and foamed into the insulation of all storage chamber walls, there are the evaporating pipes, in order to grant the maximum temperature stability and uniformity. All the used components are industrial grade granting the maximum reliability
- **Defrosting** : manual. Through a discharging pipe located in the lower frontal part of the freezer, is facilitated the water draining
- **Refrigerant** : CFC- and HCFC-free
- **Refrigeration** : static, with evaporating pipes throughout all the chamber in order to grant maximum temperature stability and uniformity
- **Temperature range** : infinitely adjustable between -10°C and -26°C, granted at ambient temperature up +40°C
- **Voltage (V/ph/Hz)** : 220-230/1/50
- **Plug** : Schuko type
- **Gross capacity (litres)** : 380
- **Net capacity (litres)** : 360
- **Dimensions (W x D x H cm)** : 157 x 70 x 86 (handle included in the depth, 4 cm)
- **Net weight (Kg)** : 80
- **Packed dimensions (W x D x H cm)** : 170 x 80 x 115 (1,57 m³)
- **Gross weight (Kg)** : 100



ESSE3 srl, Via Garibaldi 30
14022 Castelnuovo D.B. (AT)
Tel +39 011 99 27 706
Fax +39 011 99 27 506
e-mail: danielec@esse3-medical.com
web: www.esse3-medical.com

